

Superior

DEEP CYCLE

Performance



- 100% maintenance-free
- Fully sealed (Spill Proof)
- AGM (Absorbed Glass Mat)
- Faster re-charge time
- Deep cycle 100AH & 120AH
- Greater life cycle
- Shock & vibration Resistant
- Approved for inside caravan use



CHARACTERISTICS

DC 12-100

Nominal Voltage		12 V
Capacity 25°C (77°F)	20 hour rate (5.0A)	100 AH
	5 hour rate (16.4A)	82 AH
	1 hour rate (59.9A)	59.9 AH
	40°C (104°F)	102%
Capacity Affected by Temperature	25°C (77°F)	100%
	0°C (32°F)	82%
	-15°C (5°F)	65%
	after 3 month storage	90%
Self Discharge 25°C (77°F) Capacity	after 6 month storage	80%
	after 12 month storage	62%

DC 12-120

Nominal Voltage		12 V
Capacity 25°C (77°F)	20 hour rate (6.0A)	120 AH
	10 hour rate (11.2A)	112 AH
	5 hour rate (19.6A)	98 AH
	40°C (104°F)	102%
Capacity Affected by Temperature	25°C (77°F)	100%
	0°C (32°F)	82%
	-15°C (5°F)	65%
	after 3 month storage	91%
Self Discharge 25°C (77°F) Capacity	after 6 month storage	82%
	after 12 month storage	64%

PACKAGING

DC 12-100

Battery Dimensions (mm)

L	W	H	TH
307	169	211	227

Weight

Gross Weight

29.55 kgs

DC 12-120

Battery Dimensions (mm)

L	W	H	TH
331	175	214	218

Weight

Gross Weight

32.85 kgs